


### Hotwater High-Pressure Cleaner ETRONIC II Series, oil-heated

- Mobile hotwater Unit for professional use - oil-heated
- Metal-Chassis and impact-resistant Cover for long durability
- **ETRONIC II - System:**
- TSS-System with Pump Off-Delay
- Burner-On Delay 2 s
- 24 V Safety-Circuit
- Leakage-Recognition
- Unit Total-Switch Off
- Hours-Counter
- Low-Water Cut-Off
- Low-Fuel Cut-Off
- Flame-Monitor with Photocell
- Steam-Stage
- 2-Stage Switch Pump-Burner On/Off
- Transparent Containers for visual level control
- Horizontal Heatexchanger
- Flame - Failure Lamp



Type	Waterflow [l/h]	Pressure [bar]	Temperature [°C]	Connected Load [kW]	Order-No.
HD 723* Etronic II	330-720	30-120	30-150	1~230V-3.6	496
HD 840 Etronic II	330-720	30-160	30-150	3~400V-4.4	408
HD 940 Etronic II	330-840	30-180	30-150	3~400V-5.0	442
HD 1140 Etronic II	330-1000	30-230	30-150	3~400V-7.9	410
HD 1240 Etronic II	330-1200	30-165	30-150	3~400V-7.9	411

\*13A-UK-Version: 330-720 l/h, 30-110 bar